



## Allegany County Emergency Services Board Tanker Checklist

YES	NO	#	Apparatus/Equipment Requirements
		1	All apparatus shall meet Maryland Department of Transportation Standards – lighting, axle loads, tire size, frame capacities, height, length, width, etc. Annual DOT inspection paperwork shall be carried on the apparatus.
		2	Shall be equipped with the appropriate emergency vehicle warning devices required by the Maryland Motor Vehicle Code, including functional emergency warning lights and emergency audible warning devices.
		3	(2) or more-wheel chocks, mounted or stored in readily accessible locations
		4	(1) Traffic vest for each seating position, to comply with ANSI/ISEA 207 and have a five-point breakaway feature.
		5	(4) Traffic control devices (ie: flares, cones, etc.)
		6	(1) Allegany County Mobile Radio provided by DES
		7	(1) Allegany County Portable Radio per riding position.
		8	The apparatus shall be equipped with a fire pump that has a minimum rated capacity of 750 GPM.
		9	The pumper shall be equipped with a water tank that has a minimum certified capacity of 1500 gallons.
		10	200 ft of 2 1/2 inch or larger fire hose
		11	100 ft of 1 1/2 inch, 1 3/4 inch, or 2-inch fire hose
		12	(1) Handline nozzles, 95 GPM minimum
		13	<p>Suction Hose or Supply Hose</p> <ul style="list-style-type: none"><li>a) Minimum of 20 ft of suction hose or 15 ft of supply hose shall be carried.<ul style="list-style-type: none"><li>i) Where suction hose is provided, a suction strainer shall be furnished.</li><li>ii) Where supply hose is provided, it shall have couplings compatible with local hydrant outlet connection on one end and the pump intake on the other.</li><li>iii) If the supply hose carried does not use sexless couplings, an additional double female and double male adapter shall be carried</li><li>iv) If the supply hose carried has other than 2 1/2 inch NH threads, adapters shall be carried</li></ul></li></ul>
		14	If the mobile water supply apparatus is equipped with a fire pump and none of the pump intakes are valved, a hose appliance that is equipped with one or more gated intakes with female swivel connections compatible with the supply hose used on one side and a swivel connection with pump intake threads on the other side shall be carried. Any intake connection larger than 3 inches shall include a pressure relief device
		15	If the apparatus does not have a 2 1/2 inch intake with NH threads, an adapter from 2 1/2 inch NH female to a pump intake shall be carried
		16	(1) Self-contained breathing apparatus (SCBA) for each assigned seating position, but not fewer than four, mounted in brackets fastened to the apparatus or stored in containers supplied by the manufacturer

		17	(1) Spare SCBA cylinder for each SCBA carried, each mounted in a bracket fastened to the apparatus or stored in a specially designed storage space
		18	(2) Portable hand lights
		19	(1) Dry chemical portable fire extinguisher with a minimum 80-B:C rating
		20	(2) Spanner Wrenches
		21	(1) Adjustable Hydrant Wrenches
		22	(1) 2 1/2" Double Female couplings
		23	(1) 2 1/2" Double Male couplings
		24	(1) Rubber Mallet

Y E S	NO	#	Apparatus/Equipment Recommended (But not required)
		25	(1) Fire Extinguisher CO2
		26	(1) 2 1/2 gallon or larger water extinguisher
		27	(1) Bolt Cutters with 7/16" minimum cut
		28	(1) Crowbar, 36 inch minimum
		29	(1) Halligan-type tool
		30	(1) Fire service claw tool (ie: Halligan, A-Tool, etc.)
		31	(1) 2 1/2 inch hydrant valve
		32	(4) Ladder Straps, rope, or chain hose tools
		33	(1) 150 feet of 9,000 lb. tensile strength Kernmantle Life Line (Utility Ropes at the discretion of the Fire Department)
		34	(1) 150 ft length of utility rope having a breaking strength of at least 5000 lbs
		35	(2) Shovel (1-pointed & 1-Scoop)
		36	Toolbox with hammers, wrenches, screwdrivers, and other assorted tools
		37	(1) 1500-gallon collapsible, portable tank.
		38	(1) Portable pump
		39	(1) Water transfer device to be used between portable tanks.
		40	Hose adapters for water supply connections
		41	(5) fluorescent orange traffic cones not less than 28 inches in height, each equipped with a 6-inch retroreflective white band no more than 4 inches from the top of the cone and an additional 4-inch retroreflective white band 2 inches below the 6inch band.
		42	First aid kit large enough to carry all the required items below: b) 12 - Sterile gauze pads 4x4 c) 4 - Sterile dressings 5x9 d) 1 - Hemostatic impregnated dressing e) 8 - Rolls Self-adhering gauze bandages (various sizes 2" to 6") f) 4 - Cravats (triangular bandages) minimum 36"x36" g) 2 - Cold Packs h) 1 - Bottle normal saline or sterile water i) 2 - Commercially available tourniquet capable of stopping arterial blood flow j) 1 - Ring Cutter (Optional) k) 1 - Bandage scissors or rescue shears l) 1 - Penlight m) 1 - Stethoscope n) 1 - Glucometer Kit - with lancets, test strips, alcohol wipes, and band-aids (Optional) o) 1 - Adult Regular B/P Cuff

			p) 1 – Adult Large B/P Cuff q) 1 – Child B/P Cuff r) 6 – Pairs Non-Latex Gloves s) 1 – Portable Sharps Container t) Pulse Oximeter (Optional)
	43	(1)	Automated external defibrillator (AED)

Date:	Pass:		Fail:	
Company Name:				
Unit Number:	Re-Test Date:		Pass:	Fail:
Equipment Checked By:	Fire Dept. Representative:			